


NEW

POWER Wrap

Like a Seal Of Steel!

PIPE REPAIR

Water Activated Fiberglass Wrap
SETS LIKE STEEL!



REPAIR ALMOST ANY MATERIAL & PIPES UP TO 6" DIAMETER



PIPE & PLUMBING



POOL & SPA REPAIRS



SPRINKLER SYSTEMS



BOAT REPAIRS



AUTOMOTIVE REPAIRS



HYDRAULIC LINE REPAIRS



**NO TOOLS
NEEDED!**



**EPA
APPROVED!**



**ANSI/
NSF 61**



**CURES IN
30 MIN!**



**STRONG!
600 PSI**

FAST & EASY

REPAIRS:

- Copper • Rubber • Plastics
- Fiberglass • PVC Pipe
- Galvanized • Concrete • Etc.

www.fernco.com





Pow-R Wrap is a strong, permanent and economical repair. Works on virtually every kind of pipe. An easy alternative to traditional methods such as cementing, soldering, welding, sleeving and replacement. Works on wet, dry, clean, dirty or corroded pipes. Even works under water...salt or fresh.

Perfect for repairing:

- Copper
- Ruber
- Concrete
- Plastics
- Fiberglass
- And MORE!
- PVC Pipe
- Galvanized

Ideal for all fluid bearing pipes and hoses:

- Water
- Sewage
- Air
- Steam
- Fuel
- Hydraulics

Recommended for structural repairs to:

- Brackets
- Mufflers
- Fencing
- Supports
- Exhaust Pipes
- Tools

**FAST
AND
EASY
TO
INSTALL**



1. Apply Epoxy Putty



2. Immerse Wrap in Water



3. Wrap Pipe



4. Tighten for Approx 4 Min

EACH KIT CONTAINS:

- Resin impregnated fiberglass tape in foil bag
- Epoxy putty to enhance repairs
- 1 pair of protective gloves
- Complete installation instructions

TECHNICAL INFORMATION

FormImpregnated Fiberglass Cloth
 Color.....Grey
 Fabrication MethodWet Lay-Up
 Number of Wraps Required8 Minimum for High Pressure
 Cure Cycle @ 70°F/21°C.....30 Minutes (wet)
 Hardness - Cured Laminate53 Barcol
 Heat Resistance1197°F/647°C
 Dielectric Strength16,969
 Line Pressures.....600PSI/40KPA
 Shelf Life.....Unlimited when properly stored

MECHANICAL RESISTANCE

MEASURE	METHOD	PSI	KPA
Flexural Strength	ASDN D 709-71	16,100	1,073
Tensile Strength	ASTM D 638	24,000	1,660
Compression Strength	ASTM D 695-77	26,600	1,773
Temperature Cycle Test	4 layers cycled from 50°F to 90°F (10°C to 33°C): No Delamination		

APPROVED TO EPA601

Tested and approved for use with potable (drinking) water when used in accordance with instructions. Also approved to other international standards including AS4020.

TOXICITY

Contains no harmful solvents. Can be used on water and food service lines.

CHEMICAL RESISTANCE

Pow-R Wrap is chemically resistant to diesel fuel, petroleum products, halocarbon, and (after curing) alcohols.

3 KIT SIZES AVAILABLE FOR REPAIRING UP TO 6" DIA. PIPES

PART #	DESCRIPTION
FPW248CS	2" x 48" wrap to repair up to 1" diameter pipe
FPW3132CS	3" x 132" wrap to repair 1¼" to 3" diameter pipe
FPW4252CS	4" x 252" wrap to repair 3" to 6" diameter pipe



**NO TOOLS
NEEDED!**



**EPA
APPROVED!**



**ANSI/
NSF 61**



**CURES IN
30 MIN!**



**STRONG!
600 PSI**



Fernco, Inc. • Davison, MI
1-800-521-1283 • FAX: 810-653-8714

Fernco Connectors, LTD • Sarnia, Ontario
1-800-265-7518 • FAX: 519-332-8610

Fernco, Inc. West • Sparks, NV
1-800-232-3092 • FAX: 775-358-3547